

**DuPont™ SUVA® HP80 Refrigerant**

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	DuPont™ SUVA® HP80 Refrigerant
Product Grade/Type	:	ASHRAE Refrigerant number designation: R-402A
MSDS Number	:	130000050991
Product Use	:	Refrigerant
Manufacturer	:	DuPont 1007 Market Street Wilmington, DE 19898
Product Information	:	1-800-441-7515 (outside the U.S. 1-302-774-1000)
Medical Emergency	:	1-800-441-3637 (outside the U.S. 1-302-774-1139)
Transport Emergency	:	CHEMTREC: 1-800-424-9300 (outside the U.S. 1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Misuse or intentional inhalation abuse may lead to death without warning.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Rapid evaporation of the liquid may cause frostbite.

Potential Health Effects

- | | | |
|------|---|---|
| Skin | : | Contact with liquid or refrigerated gas can cause cold burns and frostbite. |
| Eyes | : | Contact with liquid or refrigerated gas can cause cold burns and frostbite. |


DuPont™ SUVA® HP80 Refrigerant

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

Inhalation : Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.
 Other symptoms potentially related to misuse or inhalation abuse are: Anaesthetic effects, Light-headedness, dizziness, confusion, incoordination, drowsiness, or unconsciousness, irregular heartbeat with a strange sensation in the chest, heart thumping, apprehension, feeling of fainting, dizziness or weakness.
 Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Carcinogenicity

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Pentafluoroethane (HFC-125)	354-33-6	60 %
Chlorodifluoromethane (HCFC-22)	75-45-6	38 %
Propane	74-98-6	2 %

SECTION 4. FIRST AID MEASURES

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Take off all contaminated clothing immediately. Consult a physician. Wash contaminated clothing before re-use. Treat for frostbite if necessary by gently warming affected area.

Eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Consult a physician if necessary.

**DuPont™ SUVA® HP80 Refrigerant**

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

Inhalation	: Remove from exposure, lie down. Move to fresh air. Keep patient warm and at rest. Artificial respiration and/or oxygen may be necessary. Consult a physician.
Ingestion	: Is not considered a potential route of exposure.
General advice	: Never give anything by mouth to an unconscious person. When symptoms persist or in all cases of doubt seek medical advice.
Notes to physician	: Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

SECTION 5. FIREFIGHTING MEASURES

Flammable Properties	
Flash point	: does not flash
Lower explosion limit	: Method : None per ASTM E681
Upper explosion limit	: Method : None per ASTM E681
Fire and Explosion Hazard	: Cylinders are equipped with pressure and temperature relief devices, but may still rupture under fire conditions. Decomposition may occur. Contact of welding or soldering torch flame with high concentrations of refrigerant can result in visible changes in the size and colour of the torch flame. This flame effect will only occur in concentrations of product well above the recommended exposure limit. Therefore stop all work and ventilate to disperse refrigerant vapors from the work area before using any open flames.

**DuPont™ SUVA® HP80 Refrigerant**

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

This substance is not flammable in air at temperatures up to 100 deg. C (212 deg. F) at atmospheric pressure. However, mixtures of this substance with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. This substance can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing this substance and air, or this substance in an oxygen enriched atmosphere become combustible depends on the inter-relationship of 1) the temperature 2) the pressure, and 3) the proportion of oxygen in the mixture. In general, this substance should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment. For example this substance should NOT be mixed with air under pressure for leak testing or other purposes. Experimental data have also been reported which indicate combustibility of this substance in the presence of certain concentrations of chlorine.

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Firefighting Instructions : Use water spray or fog to protect the fire fighters and to cool container. Self-contained breathing apparatus (SCBA) is required if containers rupture and contents are released under fire conditions.
Water runoff should be contained and neutralized prior to release.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

- Accidental Release Measures : Ventilate area, especially low or enclosed places where heavy vapours might collect. Self-contained breathing apparatus (SCBA) is required if a large release occurs. Avoid open flames and high temperatures.

SECTION 7. HANDLING AND STORAGE

- Handling (Personnel) : Avoid breathing vapours or mist. Avoid skin or eye contact with liquid. Use sufficient ventilation to keep employee exposure below recommended limits. Wash hands thoroughly after handling.



DuPont™ SUVA® HP80 Refrigerant

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

Storage : Store in a clean, dry place. Do not heat above 52° C (125° F).

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls : Refrigerant concentration monitors may be necessary to determine vapour concentrations in work areas prior to use of torches or other open flames, or if employees are entering enclosed areas. Use sufficient ventilation to keep employee exposure below recommended limits. Local exhaust should be used when large amounts are released. Mechanical ventilation should be used in low or enclosed places.

Personal protective equipment
Respiratory protection : Under normal manufacturing conditions, no respiratory protection is required when using this product.

Hand protection : Additional protection: Impervious gloves

Eye protection : Wear safety glasses with side shields. Additionally wear a face shield where the possibility exists for face contact due to splashing, spraying or airborne contact with this material.

Protective measures : Self-contained breathing apparatus (SCBA) is required if a large release occurs.

Exposure Guidelines
Exposure Limit Values
Pentafluoroethane
AEL *

(DUPONT) 1,000 ppm 8 & 12 hr. TWA

Chlorodifluoromethane
TLV

(ACGIH) 1,000 ppm TWA

Propane
PEL:

(OSHA) 1,000 ppm 1,800 mg/m3 8 hr. TWA

TLV

(ACGIH) 1,000 ppm TWA

**DuPont™ SUVA® HP80 Refrigerant**

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquefied gas
Color	: clear, colourless
Odor	: slight, ether-like
pH	: neutral
Boiling point	: -48.9 °C (-56.0 °F)
% Volatile	: 100 %
Vapour Pressure	: 13,499 hPa at 25 °C (77 °F)
Specific gravity	: 1.15 at 25 °C (77 °F)
Water solubility	: not determined
Vapour density	: 3.6 at 25 °C (77 °F) and 1013 hPa (Air = 1.0)
Evaporation rate	: > 1 (CCL4=1.0)

SECTION 10. STABILITY AND REACTIVITY

Stability	: Stable at normal temperatures and storage conditions.
Conditions to avoid	: Avoid open flames and high temperatures.
Incompatibility	: Alkali metals Alkaline earth metals, Powdered metals, Powdered metal salts
Hazardous decomposition products	: Decomposition products are hazardous., The exact nature of the decomposition products will depend upon exposure conditions - temperature, access to oxygen, high temperatures (open flames, glowing metal surfaces, etc.) forming hydrochloric and hydrofluoric acids, and possibly carbonyl halides., These materials are toxic and irritating., Avoid contact with decomposition products
Hazardous reactions	: Polymerization will not occur.


DuPont™ SUVA® HP80 Refrigerant

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

SECTION 11. TOXICOLOGICAL INFORMATION
Pentafluoroethane (HFC-125)

Dermal	:	not applicable
Oral	:	not applicable
Inhalation 4 h LC50	:	> 800000 ppm , rat
Inhalation	:	dog Cardiac sensitization
Skin irritation	:	No skin irritation, Not tested on animals Not expected to cause skin irritation based on expert review of the properties of the substance.
Eye irritation	:	No eye irritation, Not tested on animals Not expected to cause eye irritation based on expert review of the properties of the substance.
Skin sensitization	:	Does not cause skin sensitization., Not tested on animals Not expected to cause sensitization based on expert review of the properties of the substance. There are no reports of human respiratory sensitization.
Repeated dose toxicity	:	Inhalation rat No toxicologically significant effects were found.
Carcinogenicity	:	Overall weight of evidence indicates that the substance is not carcinogenic.
Mutagenicity	:	Did not cause genetic damage in animals. Did not cause genetic damage in cultured mammalian cells. Did not cause genetic damage in cultured bacterial cells.
Reproductive toxicity	:	Evidence suggests the substance is not a reproductive toxin in animals. Information given is based on data obtained from similar substances.
Teratogenicity	:	Animal testing showed no developmental toxicity.

**DuPont™ SUVA® HP80 Refrigerant**

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

Further information	:	Cardiac sensitisation threshold limit : 490000 mg/m3
Chlorodifluoromethane (HCFC-22)		
Dermal	:	not applicable
Oral	:	not applicable
Inhalation 4 h LC50	:	220000 ppm , rat
Inhalation	:	dog Cardiac sensitization
Skin irritation	:	No skin irritation, rabbit Not expected to cause skin irritation based on expert review of the properties of the substance.
Eye irritation	:	No eye irritation, rabbit Not expected to cause eye irritation based on expert review of the properties of the substance.
Skin sensitization	:	Did not cause sensitization on laboratory animals., guinea pig Not expected to cause sensitization based on expert review of the properties of the substance.
Repeated dose toxicity	:	Inhalation mouse No toxicologically significant effects were found.
Carcinogenicity	:	An increased incidence of tumours was observed in some laboratory animals but not in others. Overall weight of evidence indicates that the substance is not carcinogenic.
Mutagenicity	:	Did not cause genetic damage in animals. Did not cause genetic damage in cultured mammalian cells. Experiments showed mutagenic effects in cultured bacterial cells.
Reproductive toxicity	:	Evidence suggests the substance is not a reproductive toxin in animals.
Teratogenicity	:	Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.


DuPont™ SUVA® HP80 Refrigerant

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

Propane	Further information	: Cardiac sensitisation threshold limit : 175000 mg/m3
	Dermal	: not applicable
	Oral	: not applicable
	Inhalation 4 h LC50	: > 200000 ppm , rat
	Inhalation	: dog Cardiac sensitization
	Skin irritation	: not applicable
	Eye irritation	: not applicable
	Skin sensitization	: not applicable
	Repeated dose toxicity	: Inhalation rat No toxicologically significant effects were found.
	Mutagenicity	: Did not cause genetic damage in cultured bacterial cells.
	Further information	: Cardiac sensitisation threshold limit : 180369 mg/m3

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity	
Pentafluoroethane (HFC-125)	
96 h LC50	: Oncorhynchus mykiss (rainbow trout) > 81.8 mg/l Information given is based on data obtained from similar substances.
96 h LC50	: Danio rerio (zebra fish) > 200 mg/l Information given is based on data obtained from similar substances.
96 h LC50	: Oncorhynchus mykiss (rainbow trout) 450 mg/l Information given is based on data obtained from similar substances.
72 h EC50	: Pseudokirchneriella subcapitata (green algae) > 118 mg/l


DuPont™ SUVA® HP80 Refrigerant

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

Information given is based on data obtained from similar substances.

72 h EC50 : Pseudokirchneriella subcapitata (green algae) > 114 mg/l
Information given is based on data obtained from similar substances.

96 h EC50 : Algae 142 mg/l
Information given is based on data obtained from similar substances.

48 h EC50 : Daphnia magna (Water flea) > 200 mg/l
Information given is based on data obtained from similar substances.

48 h EC50 : Daphnia magna (Water flea) > 97.9 mg/l
Information given is based on data obtained from similar substances.

Chlorodifluoromethane (HCFC-22)

96 h LC50 : Zebra fish 777 mg/l

96 h EC50 : Algae 250 mg/l

48 h EC50 : Daphnia magna (Water flea) 433 mg/l

Environmental Fate

Chlorodifluoromethane (HCFC-22)

Biodegradability : According to the results of tests of biodegradability this product is not readily biodegradable.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal : Can be used after re-conditioning. Recover by distillation or remove to a permitted waste disposal facility. Comply with applicable Federal, State/Provincial and Local Regulations.

Environmental Hazards : Empty pressure vessels should be returned to the supplier.

SECTION 14. TRANSPORT INFORMATION

DOT UN number : 3163

10 / 12


DuPont™ SUVA® HP80 Refrigerant

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

IATA_C	Proper shipping name	: Liquefied gas, n.o.s. (Chlorodifluoromethane, Pentafluoroethane)
	Class	: 2.2
	Labelling No.	: 2.2
	UN number	: 3163
IMDG	Proper shipping name	: Liquefied gas, n.o.s. (Chlorodifluoromethane, Pentafluoroethane)
	Class	: 2.2
	Labelling No.	: 2.2
	UN number	: 3163
	Proper shipping name	: Liquefied gas, n.o.s. (Chlorodifluoromethane, Pentafluoroethane)
	Class	: 2.2
	Labelling No.	: 2.2

SECTION 15. REGULATORY INFORMATION

SARA 313 Regulated Chemical(s)	: Chlorodifluoromethane
California Prop. 65	: Chemicals known to the State of California to cause cancer, birth defects or any other harm: none known
PA Right to Know Regulated Chemical(s)	: Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances): Propane , Chlorodifluoromethane
NJ Right to Know Regulated Chemical(s)	: Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as carcinogens, mutagens or teratogens): Propane , Chlorodifluoromethane

SECTION 16. OTHER INFORMATION

HMIS



DuPont™ SUVA® HP80 Refrigerant

Version 2.1

Revision Date 08/02/2011

Ref. 130000050991

Health	:	1
Flammability	:	0
Reactivity/Physical hazard	:	1
PPE	:	Personal Protection rating to be supplied by user depending on use conditions.

SUVA is a registered trademark of E. I. du Pont de Nemours and Company

Before use read DuPont's safety information.

For further information contact the local DuPont office or DuPont's nominated distributors.

® DuPont's registered trademark

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.