

SAFETY DATA SHEET

WELD-ON® 505™ KEY TITE Low VOC Pipe Joint Compound

SECTION I - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WELD-ON® 505™ KEY TITE Low VOC Pipe Joint Compound

PRODUCT USE: Pipe Thread Sealant

SUPPLIER: MANUFACTURER: **IPS** Corporation

17109 South Main Street, Carson, CA 90248-3127 P.O. Box 379, Gardena, CA 90247-0379

EMERGENCY: Transportation: CHEMTEL Tel. 800.255-3924, 813-248-0585 (International) Medical: Tel. 800.451.8346, 760.602.8703 3E Company (International)

SECTION 2 - HAZARDS IDENTIFICATION

CLASSIFICATION:

H223: Flammable material

H315: Causes skin irritation H320: Causes eye irritation

Stoddard Solvent

H303: May be harmful if swallowed

H336: May cause drowsiness or dizziness

Health Environmental Physical Not Available Acute Toxicity: Not Available Acute Toxicity: Flammable Liquid Category 4 Skin Irritation: Category 3 Chronic Toxicity: Not Available No Skin Sensitization:

Eye: LABEL:

Category 2B



OR



Signal Word: Danger

CLASS B, DIVISION 3 WHMIS CLASSIFICATION: Combustible Liquid

Date Revised: DEC 2011

Supersedes: SEP 2010

Hazard Statements Precautionary Statements

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking

P261: Avoid breathing dust/fume/gas/mist/vapors/spray

P280: Wear protective gloves/protective clothing/eye protection/face protection

P337+P313: Get medical advice/attention

P403+P233: Store in a well ventilated place. Keep container tightly closed P501: Dispose of contents/container in accordance with local regulation

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

CONCENTRATION REACH Pre-registration Number % by Weight 8052-41-3 222-489-3 Under development

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing. Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).

indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 4 - FIRST AID MEASURES

Contact with eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately

Skin contact: Wash skin with soap and water. If irritation develops, get medical attention

Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration, preferable mouth to mouth. Seek medical advice.

Ingestion: Do not induce vomiting and give 1 or 2 glasses of water. Seek medical advice immediately.

SECTION 5 - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Foam, CO2, dry chemical or water fog. HMIS 0-Minimal 1-Slight Unsuitable Extinguishing Media: Water can be used to keep containers cool Health and to flush spills away from fire exposure. 2 2-Moderate Flammability **Exposure Hazards:** 0 3-Serious Inhalation. Reactivity **Combustion Products:** Smoke, fumes, oxides of carbon. PPF R 4-Severe

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing. Protection for Firefighters:

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Clear all personnel from area. Do not breathe vapors. Ventilate area of leak or spill. Wear protective equipment Personal precautions: positive pressure self contained or air supplied breathing apparatus. Follow confined space entry procedures.

Environmental Precautions: Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.

Methods for Cleaning up: Recover free product. Add sand, earth or some other suitable adsorbent.

Materials not to be used for clean up: Not available

SECTION 7 - HANDLING AND STORAGE

Handling: Avoid breathing of vapor, avoid contact with eyes, skin and clothing. Do not swallow. Use with adequate ventilation.

Do not eat, drink or smoke while handling.

Store in cool dry area in original or equivalent container in acordance with all apllicable regulations. Do not expose to extreme heat or flame. Store below 55.5°C (150°F). Storage:

Follow all precautionary information on container label, product bulletins and solvent bonding literature

SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS: OSHA PEL OSHA STEL: Componen ACGIH TLV ACGIH STEL Stoddard Solvent 500 ppm

Engineering Controls: Use with adequate ventilation

Monitoring: Maintain breathing zone airborne concentrations below exposure limits.

Personal Protective Equipment (PPE):

Eye Protection: Use chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin Protection: Oil impervious gloves for prolonged or repeated skin contact.

Respiratory Protection: Prevent inhalation of the solvents. Use in a well-ventilated room. Open doors and/or windows to ensure airflow and air changes. Use local

exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above.

Filename: W-O505 KEY TITE_LoVoc_12-11.xls Page 1 of 2

12/14/2011 3:47 PM



SAFETY DATA SHEET

WELD-ON® 505™ KEY TITE Low VOC Pipe Joint Compound

Date Revised: DEC 2011 Supersedes: SEP 2010

No data

No data

No data

No data

No data

No data

LEL: Not Available

UEL: Not Available

None

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Viscous, green liquid Odor: Linseed-like ph: Not Applicable Melting/Freezing Point: No data

Boiling Point: No data

71 °C (160 °F) T.C.C. based on Stoddard Solvent Flash Point: Specific Gravity: >1 @23°C (73.4°F)

Solubility: > 1%

Partition Coefficient n-octanol/water: **Auto-ignition Temperature:** Not Available **Decomposition Temperature:**

Not Applicable **VOC Content:**

Not Available Vapor Pressure: Vapor Density:

Other Data: Viscosity: When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: ≤250 g/l.

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable

Hazardous decomposition products: Oxides of carbon, smoke, fumes Conditions to avoid: Extreme heat Incompatible Materials: Strong oxidizers, acids

SECTION 11 - TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Ingestion, Eye and Skin Contact

Acute symptoms and effects:

Inhalation: May case dizziness, headache, loss of coordination and breathing difficulty.

Eve Contact: May cause tearing, redness, blurred vision and irritation. Skin Contact: May case drying of skin, irritation and dermatitis.

Ingestion: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic (long-term) effects: None known to humans Toxicity: LD₅₀

LC₅₀ Stoddard Solvent No data No data

Reproductive Effects Sensitization to Product Synergistic Products Teratogenicity Mutagenicity **Embryotoxicity** Not Established Not Established Not Established Not Established Not Established Not Established

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No data Mobility: No data Degradability: No data No data Bioaccumulation:

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert.

SECTION 14 - TRANSPORT INFORMATION

Proper Shipping Name: Hazard Class: Flammable Liquid, Toxic, Stoddard Solvent

Secondary Risk: 6.1 (Stoddard Solvent)

Identification Number: UN 1992

Packing Group: PG III

Label Required: Class 3 Flammable Liquid

Class 6.1 Toxic

Marine Pollutant:

SECTION 15 - REGULATORY INFORMATION

UN NUMBER/PACKING GROUP:

Precautionary Label Information: Flammable, Irritant

TDG CLASS:

SHIPPING NAME:

Symbols: F. Xi Risk Phrases:

R10: Flammable

R36/37: Irritating to eyes and respiratory system.

R38: Irritating to skin.

S2: Keep out of the reach of children.

S7:Keep container tightly closed when not in use S9: Keep container in a well-ventilated place.

S16: Keep away from sources of ignition. No smoking.

S23/25: Toxic by inhalation and if swallowed.

Ingredient Listings: USA TSCA, Europe EINECS, Canada DSL, Australia, AICS, Korea ECL/TCCL, Japan MITI (ENCS)

EXCEPTION for Ground Shipping

Consumer Commodity: Depending on packaging, these quantities may qualify under DOT as "ORM-D"

TDG INFORMATION

DOT Limited Quantity: Up to 4L per inner packaging, 30 kg gross weight per package.

Odor Threshold:

Boiling Range:

Flammability:

Evaporation Rate:

Flammability Limits:

UN 1992, PG III

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking

R67: Vapors may cause drowsiness and dizziness

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S29: Do not empty into drains.

S33: Take precautionary measures against static discharges

S37: Wear suitable gloves.

S46: If swallowed, seek medical advise immediately and show this container or label.

S51: Use only in well ventilated areas.

SECTION 16 - OTHER INFORMATION

Specification Information:

Safety Phrases:

Department issuing data sheet: IPS. Safety Health & Environmental Affairs E-mail address:

<EHSinfo@ipscorp.com>

All ingredients are compliant with the requirements of the European Directive on BoHS (Restriction of Hazardous Substances).

FLAMMABLE LIQUID 3. TOXIC 6.1

Flammable Liquid, Toxic, Stoddard Solvent

Training necessary: Yes, training in practices and procedures contained in product literature.

Reissue date / reason for reissue: 12/14/2011 / Updated GHS Standard Format

Intended Use of Product: Pipe Thread Sealant

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.

12/14/2011 3:47 PM